

IN THE CLAIMS:

1(Previously Presented). An oven for cooking food, the oven comprising:
an enclosure for receiving food to be heated and for containing a cooking atmosphere, the enclosure comprising two horizontal walls forming respectively a bottom wall and a top wall, interconnected by at least two vertical side walls, the enclosure being closed by at least one door that is likewise vertical, and communicating with the outside via an exhaust opening for exhausting gas inside the enclosure and at a pressure above atmospheric pressure; and
a heater device for heating the cooking atmosphere;
the oven being characterized by the fact that it comprises:
a regulation chamber, filled at least in part with a liquid of volume adapted to vary between a high level and a low level, the regulation chamber communicating with the enclosure via an air inlet; and
an air admission duct which extends between a high end and a low end, the high end opening out outside the regulation chamber and the enclosure, and the low end being closed by the liquid in the regulation chamber when the level of the liquid corresponds substantially to its high level.

2(Previously Presented). An oven according to claim 1, including an evacuation chamber filled at least in part with a liquid of volume that is adapted to vary between a high level and a low level, said evacuation chamber communicating with the regulation chamber during oven cooking operations.

3(Previously Presented). An oven according to claim 2, including an evacuation tube extending between the exhaust opening and a high end opening out into the evacuation chamber above the high and low liquid levels.

4(Previously Presented). An oven according to claim 3, including a chimney extending between a first end communicating with the outside of the evacuation chamber and a second end coming over the high level of the liquid, said second end allowing gas under positive pressure to escape from the enclosure via the evacuation tube.

5(Previously Presented). An oven according to claim 2, including a regulator itself comprising the regulation chamber and the evacuation chamber, these two chambers constituting side by side volumes that are separated from each other at least in part via a partition internal of the regulator and that communicate with each other via a narrow passage in the partition adapted to allow the liquid to flow between these two chambers.

6(Previously Presented). An oven according to claim 2, including, in the evacuation chamber, a first temperature probe for measuring the temperature of the gas coming from the exhaust opening, and in the regulation chamber, a second temperature probe for measuring the temperature of the gas coming into the enclosure via the air inlet.

7(Previously Presented). An oven according to claim 2, comprising in the evacuation chamber, a first temperature probe for measuring the temperature of the gas coming from the exhaust opening, and a second temperature probe placed below the low level of the liquid in the evacuation chamber.

8(Previously Presented). An oven according to claim 6, including calculation means for determining the relative humidity in the oven as a function of the temperatures measured by the first and second probes.

9(Previously Presented). An oven according to claim 1, including a fan disposed inside the enclosure to stir the cooking atmosphere heated by the heater device, said fan creating a suction zone inside the enclosure, the air inlet being situated substantially in the suction zone of the fan.

10(Previously Presented). An oven according to claim 1, including vapour-producing means suitable for delivering water vapour into the enclosure, the vapour-producing means external of the regulation chamber.

11(Previously Presented). An oven according to claim 1, in which the exhaust opening for exhausting gas under positive pressure inside the enclosure is situated beneath the heater device.

12(Previously Presented). An oven according to claim 1, in which the exhaust opening opens out substantially in the lowest point of the bottom wall.

13(Previously Presented). An oven according to claim 1, in which the exhaust opening communicates with a siphon adapted to evacuate liquids and condensates from the enclosure while preventing cold air from rising into the enclosure.

14-100(Canceled).

101(Previously Presented). An oven for cooking food, the oven comprising:

an enclosure for receiving food to be heated and for containing a cooking atmosphere, the enclosure comprising a bottom wall and a top wall, interconnected by at least two side walls, the enclosure being closed by at least one door, and communicating with the outside via an exhaust opening for exhausting gas inside the enclosure and at a pressure above atmospheric pressure;
and

a heater device for heating the cooking atmosphere;

a regulation chamber, filled at least in part with a liquid of volume adapted to vary between a high level and a low level, the regulation chamber communicating with the enclosure via an air inlet;

an air admission duct which extends between a high end and a low end, the high end opening out outside the regulation chamber and the enclosure, and the low end being closed by the liquid in the regulation chamber when the level of the liquid corresponds substantially to its high level;

an evacuation chamber filled at least in part with a liquid of volume that is adapted to vary between a high level and a low level, said evacuation chamber communicating with the regulation chamber during oven cooking operations.